

World's Largest MT-Propeller Distributor



Piper PA-46-500TP Piper Meridian, PA-46-500TP

Quiet Fan Jet Propeller Series

Engine: P&WC PT6A-42A

Advantages: (Performance data are based on MTOW, ISA)

- Best vibration damping characteristics for almost vibration free propeller operations
- Bonded on nickel alloy leading edge for best erosion protection of the blades
- General performance improvement (10% shorter take-off distance, 4% better climb Performance, 3 kts faster in cruise)
- Approx. 3 lbs less weight than the original metal propeller
- Cooler ITT on ground with condition lever at low and high idle position
- No propeller speed restrictions on ground while operating in low idle, possibility to reduce Ng to 57% for better ground handling
- Unlimited blade life
- More ground clearance => less FODs
- FOD repairable blades
- Significant cabin noise and vibration reduction
- All models comply with the strict German noise regulations 2010- "Landeplatz" Lärmschutz Verordnung" for unrestricted airport operations in Germany and other European Countries.

STC Kit Contents: FAA STC: SA03446NY

- One 5-Blade Full Feathering Constant Speed Propeller
- One Full Composite Spinner
- One Airplane Flight Manual Supplement
- One Installation Instruction
- One Instruction For Continued Airworthiness

MTV-27-1-E-C-F-R(P)/CFR203-58d

(AFRP) P-1228-()

Doc. No. E-2168

Doc. No. E-2169

Doc. No. E-2170

 One Operation and Installation Manual ATA 61-06-10 (E-610)

Propeller Specifications:

- Full Propeller Designation
- Propeller Hub
- Blade
- Blade Design
- Propeller De-Ice
- Installed Propeller & Spinner Weight
- Diameter
- TBO

MTV-27-1-E-C-F-R(P)/ CFR203-58d

MTV-27-1-E-C-F-R(P)

Milled single-piece aluminum hub

CFR203-58d

Scimitar, light-weight natural composite

Electro-thermal de-ice boots

64,4 kg - 142 lbs 2,03 m - 79,92 in

According to SB 1 () latest issue

Replaces: 4-Blade Hartzell propeller

To learn more about this prop 866-717-1117 www.Flight-Resource.com

For other products 800-544-8594 www.McFarlaneAviation.com

