

Flight-Resource

A Division of  McFarlane

World's Largest MT-Propeller Distributor



Piper PA-28 PA-28R-201T, PA-28RT-201T

S/N: 28R-7703001 through 28R-7803374,
2803001 through 2803012, 28R-7931001
through 28R-8631005, 2831001 and 2831038

Engines: Teledyne Continental Motor
TSIO-360-F, -FB

Advantages:

- Best vibration damping characteristics for almost vibration free propeller operations
- Bonded on stainless steel leading edge for best erosion protection of the blades
- Take-off distance remains unchanged
- Enhanced climb and cruise performance by approx. 5 % (SL, ISA conditions)
- Enhanced cruise performance by 2 to 3 kts (MTOW, ISA conditions)
- Unlimited blade life
- Significant inside and outside noise reductions

STC Kit Contents: FAA STC: SA02598AT


- | | |
|---|----------------------|
| • One 3-Blade Constant Speed Propeller | MTV-12-D/188-30d |
| • One Full Composite Spinner | (AFRP) P-285-7 |
| • One Airplane Flight Manual Supplement | Doc. No. E-677-E |
| • One Operation and Installation Manual | ATA 61-01-24 (E-124) |

Propeller Specifications:

- | | |
|--|--|
| • Full Propeller Designation | MTV-12-D/188-30d |
| • Propeller Hub | MTV-12-D
Milled single-piece aluminum hub |
| • Blade 188-30d | |
| • Blade Design | Light-weight natural composite |
| • Installed Propeller & Spinner Weight | 45.6 lbs |
| • Maximum Diameter | 74 in. |
| • Minimum Diameter | 72 in. |
| • TBO | According to SB 1 () latest issue |

Replaces: Hartzell BHC-C2YF-1()F/F8459A-8R, PHC-C3YF-1()F/F7663-2R

mt-propeller



To learn more about this prop
866-717-1117
www.Flight-Resource.com

For other products
800-544-8594
www.McFarlaneAviation.com